

Durapack WHTR74 C1 rPP

Packaging Textiles



Technical Textiles


PRODUCT SPECIFICATION

TYPICAL PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE
		WARP	WEFT		
TOTAL WEIGHT		74		g/m ²	± 5 %
WIDTH		125 - 133 - 150 200 - 400		cm	± 2 cm

PRODUCT INFORMATION

TYPICAL PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE
		WARP	WEFT		
MATERIAL		PP	PP		
COUNT OF TAPES	ISO 7211/2	94	25	/10cm	± 2 %
BREAK ELONGATION	ISO 13934-1	13	10	%	± 20 %
TENSILE STRENGTH	ISO 13934-1	700	275	N/5cm	± 20 %
TISSUE WEIGHT	EN 3801	49		g/m ²	± 5 %
TISSUE COLOUR		white-transparent			
COATING MATERIAL		PP			
COATED SIDES		1			
COATING WEIGHT/SIDE	ISO 2286	25		g/m ²	± 10 %
COATING COLOUR		transparent			
LENGTH		1000		m	± 2 %

ENVIRONMENTAL IMPACT CATEGORIES

PROPERTIES	TEST METHOD	VALUE	UNIT	TOLERANCE
GLOBAL WARMING POTENTIAL (Cradle-to-Gate)	EN 15804 +A2	0,1144	kg CO2 eq./m ²	
Compared to the standard PP packaging, you reach a reduction in CO2 of 17 %.				
<div><p>Accordingly QA-CER system 2 mentioning 30% recycled content (post-industrial waste)</p></div>				

This information is not to be taken as a warranty or representation for which we assume legal responsibility.
It is offered solely for your consideration, investigation, verification and shall form no part of any contract with the customer.